

SPACE 05

STAGE Technical Data Sheet

STAGE SIZE

Length	97' 1"	29.60 m
Width	92' 2"	28.10 m
Height (to rigging point)	21' 9"	6.64 m
Area	8,991 sq ft	826.0 sq m
Undercroft Area	1512 sq ft	140.5 sp m

ELECTRICAL SUPPLY

Maximum current available 400Amps 3-phase

A variety of 13 – 32 Amp power supplies In Stage:

- 1 x 16amp single phase
- 1 x 32amp single phase
- 1 x 16amp three phase
- 10 x 13amp twin sockets

A variety of 13 – 400 Amp power supplies In Dimmer Room:

- 2 x 63amp single phase
- 2 x 63amp three phase
- 1 x 125amp three phase
- 1 x 32amp three phase

BEAM LOADING Max line load for each truss = 257kg / 0.257metric ton per metre length
 Max point load at any one point on the truss = 925kg / 0.925 metric ton spaced no closer than 3.6m / 11' 9" centres

LOADING ACCESS Stage door 3.4m x 3.3m

FLOOR TYPE Resin Floor

FLOOR LOADING 5kn/sq m

COOLING Cooling with extraction

WATER ON STAGE Belfast sink with cold water supply [non-drinking water]

CONNECTIVITY AND WIFI 5 in stage outlets, extensive site-wide wireless coverage

FIRE PROTECTION Smoke detection with isolation functionality

FIRE EXTINGUISHERS H2O, CO2, Foam

RED LIGHT Yes

BELL Yes

ACOUSTICS Fully sound insulated up to 65dB between stages and reverberation control to below 2secs. , UK,)